

Package: superml (via r-universe)

September 15, 2024

Type Package

Title Build Machine Learning Models Like Using Python's Scikit-Learn Library in R

Version 0.5.7

Maintainer Manish Saraswat <manish06saraswat@gmail.com>

Description The idea is to provide a standard interface to users who use both R and Python for building machine learning models. This package provides a scikit-learn's fit, predict interface to train machine learning models in R.

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

URL <https://github.com/saraswatmks/superml>

BugReports <https://github.com/saraswatmks/superml/issues>

Depends R(>= 3.6), R6(>= 2.2)

Imports data.table (>= 1.10), Rcpp (>= 1.0), assertthat (>= 0.2), Metrics (>= 0.1)

LinkingTo Rcpp, BH, RcppArmadillo

Suggests knitr, rlang, testthat, rmarkdown, naivebayes(>= 0.9), ClusterR(>= 1.1), FNN(>= 1.1), ranger(>= 0.10), caret(>= 6.0), xgboost(>= 0.6), glmnet(>= 2.0), e1071(>= 1.7)

RoxygenNote 7.3.1

VignetteBuilder knitr

Repository <https://saraswatmks.r-universe.dev>

RemoteUrl <https://github.com/saraswatmks/superml>

RemoteRef HEAD

RemoteSha 0d7f6aea09968267a11612475424d4635d57877c

Contents

bm_25	2
cla_train	3
Counter	3
CountVectorizer	4
dot	7
dotmat	8
GridSearchCV	9
kFoldMean	11
KMeansTrainer	13
KNNTrainer	16
LabelEncoder	20
LMTrainer	23
NBTrainer	29
normalise1d	31
normalise2d	32
RandomSearchCV	33
reg_train	35
RFTrainer	36
smoothMean	40
sort_index	41
TfidfVectorizer	42
XGBTrainer	46
Index	55

 bm_25

BM25 Matching

Description

BM25 stands for Best Matching 25. It is widely using for ranking documents and a preferred method than TF*IDF scores. It is used to find the similar documents from a corpus, given a new document. It is popularly used in information retrieval systems. This implementation is based on c++ functions hence quite optimised as well.

Usage

```
bm_25(document, corpus, top_n)
```

Arguments

document	a string for which to find similar documents
corpus	a vector of strings against which document is to be matched
top_n	top n similar documents to find

Value

a vector containing similar documents and their scores

Examples

```
docs <- c("chimpanzees are found in jungle",
          "chimps are jungle animals",
          "Mercedes automobiles are best",
          "merc is made in germany",
          "chimps are intelligent animals")

sentence <- "automobiles are"
s <- bm_25(document=sentence, corpus=docs, top_n=2)
```

cla_train	<i>cla_train</i>
-----------	------------------

Description

Training Dataset used for classification examples. This is classic titanic dataset used to predict if a passenger will survive or not in titanic ship disaster.

Usage

```
cla_train
```

Format

An object of class `data.table` (inherits from `data.frame`) with 891 rows and 12 columns.

Source

<https://www.kaggle.com/c/titanic/data>

Counter	<i>Calculate count of values in a list or vector</i>
---------	--

Description

Handy function to calculate count of values given in a list or vector

Usage

```
Counter(data, sort = TRUE, decreasing = FALSE)
```

Arguments

`data` should be a vector or list of input values
`sort` a logical value, to sort the result or not
`decreasing` a logical value, the order of sorting to be followed

Value

count of values in a list

Examples

```
d <- list(c('i','am','bad'),c('you','are','also','bad'))
counts <- Counter(d, sort=TRUE, decreasing=TRUE)
```

CountVectorizer

Count Vectorizer

Description

Creates CountVectorizer Model.

Details

Given a list of text, it generates a bag of words model and returns a sparse matrix consisting of token counts.

Public fields

`sentences` a list containing sentences
`max_df` When building the vocabulary ignore terms that have a document frequency strictly higher than the given threshold, value lies between 0 and 1.
`min_df` When building the vocabulary ignore terms that have a document frequency strictly lower than the given threshold, value lies between 0 and 1.
`max_features` Build a vocabulary that only consider the top `max_features` ordered by term frequency across the corpus.
`ngram_range` The lower and upper boundary of the range of n-values for different word n-grams or char n-grams to be extracted. All values of n such such that `min_n <= n <= max_n` will be used. For example an `ngram_range` of `c(1, 1)` means only unigrams, `c(1, 2)` means unigrams and bigrams, and `c(2, 2)` means only bigrams.
`split` splitting criteria for strings, default: " "
`lowercase` convert all characters to lowercase before tokenizing
`regex` regex expression to use for text cleaning.
`remove_stopwords` a list of stopwords to use, by default it uses its inbuilt list of standard stopwords
`model` internal attribute which stores the count model

Methods

Public methods:

- `CountVectorizer$new()`
- `CountVectorizer$fit()`
- `CountVectorizer$fit_transform()`
- `CountVectorizer$transform()`
- `CountVectorizer$clone()`

Method `new()`:

Usage:

```
CountVectorizer$new(  
  min_df,  
  max_df,  
  max_features,  
  ngram_range,  
  regex,  
  remove_stopwords,  
  split,  
  lowercase  
)
```

Arguments:

`min_df` numeric, When building the vocabulary ignore terms that have a document frequency strictly lower than the given threshold, value lies between 0 and 1.

`max_df` numeric, When building the vocabulary ignore terms that have a document frequency strictly higher than the given threshold, value lies between 0 and 1.

`max_features` integer, Build a vocabulary that only consider the top `max_features` ordered by term frequency across the corpus.

`ngram_range` vector, The lower and upper boundary of the range of n-values for different word n-grams or char n-grams to be extracted. All values of n such such that `min_n <= n <= max_n` will be used. For example an `ngram_range` of `c(1, 1)` means only unigrams, `c(1, 2)` means unigrams and bigrams, and `c(2, 2)` means only bigrams.

`regex` character, regex expression to use for text cleaning.

`remove_stopwords` list, a list of stopwords to use, by default it uses its inbuilt list of standard english stopwords

`split` character, splitting criteria for strings, default: " "

`lowercase` logical, convert all characters to lowercase before tokenizing, default: TRUE

Details: Create a new 'CountVectorizer' object.

Returns: A 'CountVectorizer' object.

Examples:

```
cv = CountVectorizer$new(min_df=0.1)
```

Method `fit()`:

Usage:

```
CountVectorizer$fit(sentences)
```

Arguments:

sentences a list of text sentences

Details: Fits the countvectorizer model on sentences

Returns: NULL

Examples:

```
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
cv = CountVectorizer$new(min_df=0.1)
cv$fit(sents)
```

Method fit_transform():

Usage:

```
CountVectorizer$fit_transform(sentences)
```

Arguments:

sentences a list of text sentences

Details: Fits the countvectorizer model and returns a sparse matrix of count of tokens

Returns: a sparse matrix containing count of tokens in each given sentence

Examples:

```
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
cv <- CountVectorizer$new(min_df=0.1)
cv_count_matrix <- cv$fit_transform(sents)
```

Method transform():

Usage:

```
CountVectorizer$transform(sentences)
```

Arguments:

sentences a list of new text sentences

Details: Returns a matrix of count of tokens

Returns: a sparse matrix containing count of tokens in each given sentence

Examples:

```
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
new_sents <- c("dark at night", 'mothers day')
cv = CountVectorizer$new(min_df=0.1)
cv$fit(sents)
cv_count_matrix <- cv$transform(new_sents)
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CountVectorizer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `CountVectorizer$new`
## -----

cv = CountVectorizer$new(min_df=0.1)

## -----
## Method `CountVectorizer$fit`
## -----

sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
cv = CountVectorizer$new(min_df=0.1)
cv$fit(sents)

## -----
## Method `CountVectorizer$fit_transform`
## -----

sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
cv <- CountVectorizer$new(min_df=0.1)
cv_count_matrix <- cv$fit_transform(sents)

## -----
## Method `CountVectorizer$transform`
## -----

sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
new_sents <- c("dark at night", 'mothers day')
cv = CountVectorizer$new(min_df=0.1)
cv$fit(sents)
cv_count_matrix <- cv$transform(new_sents)
```

dot

Dot product similarity in vectors

Description

Computes the dot product between two given vectors.

Usage

```
dot(a, b, norm = TRUE)
```

Arguments

a	numeric vector
b	numeric vector
norm	logical, compute normalised dot product, default=True

Value

numeric vector containing sdot product score

Examples

```
a <- runif(5)
b <- runif(5)
s <- dot(a, b)
```

dotmat

Dot product similarity between a vector and matrix

Description

Computes the dot product between a vector and a given matrix. The vector returned has a dot product similarity value for each row in the matrix.

Usage

```
dotmat(a, b, norm = TRUE)
```

Arguments

a	numeric vector
b	numeric matrix
norm	logical, compute normalised dot product, default=True

Value

numeric vector containing dot product scores

GridSearchCV

Grid Search CV

Description

Runs grid search cross validation scheme to find best model training parameters.

Details

Grid search CV is used to train a machine learning model with multiple combinations of training hyper parameters and finds the best combination of parameters which optimizes the evaluation metric. It creates an exhaustive set of hyperparameter combinations and train model on each combination.

Public fields

`trainer` superml trainer object, could be either XGBTrainer, RFTrainer, NBTrainer etc.

`parameters` a list of parameters to tune

`n_folds` number of folds to use to split the train data

`scoring` scoring metric used to evaluate the best model, multiple values can be provided. currently supports: auc, accuracy, mse, rmse, logloss, mae, f1, precision, recall

`evaluation_scores` parameter for internal use

Methods**Public methods:**

- [GridSearchCV\\$new\(\)](#)
- [GridSearchCV\\$fit\(\)](#)
- [GridSearchCV\\$best_iteration\(\)](#)
- [GridSearchCV\\$clone\(\)](#)

Method new():

Usage:

```
GridSearchCV$new(trainer = NA, parameters = NA, n_folds = NA, scoring = NA)
```

Arguments:

`trainer` superml trainer object, could be either XGBTrainer, RFTrainer, NBTrainer etc.

`parameters` list, a list of parameters to tune

`n_folds` integer, number of folds to use to split the train data

`scoring` character, scoring metric used to evaluate the best model, multiple values can be provided. currently supports: auc, accuracy, mse, rmse, logloss, mae, f1, precision, recall

Details: Create a new 'GridSearchCV' object.

Returns: A 'GridSearchCV' object.

Examples:

```
rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))
```

Method fit():*Usage:*

GridSearchCV\$fit(X, y)

Arguments:

X data.frame or data.table

y character, name of target variable

Details: Trains the model using grid search*Returns:* NULL*Examples:*

```
rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))

data("iris")
gst$fit(iris, "Species")
```

Method best_iteration():*Usage:*

GridSearchCV\$best_iteration(metric = NULL)

Arguments:

metric character, which metric to use for evaluation

Details: Returns the best parameters*Returns:* a list of best parameters*Examples:*

```
rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))

data("iris")
gst$fit(iris, "Species")
gst$best_iteration()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
GridSearchCV$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `GridSearchCV$new`
## -----

rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))

## -----
## Method `GridSearchCV$fit`
## -----

rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))

data("iris")
gst$fit(iris, "Species")

## -----
## Method `GridSearchCV$best_iteration`
## -----

rf <- RFTrainer$new()
gst <- GridSearchCV$new(trainer = rf,
                       parameters = list(n_estimators = c(100),
                                         max_depth = c(5,2,10)),
                       n_folds = 3,
                       scoring = c('accuracy', 'auc'))

data("iris")
gst$fit(iris, "Species")
gst$best_iteration()
```

Description

Calculates out-of-fold mean features (also known as target encoding) for train and test data. This strategy is widely used to avoid overfitting or causing leakage while creating features using the target variable. This method is experimental. If the results you get are unexpected, please report them in github issues.

Usage

```
kFoldMean(train_df, test_df, colname, target, n_fold = 5, seed = 42)
```

Arguments

train_df	train dataset
test_df	test dataset
colname	name of categorical column
target	the target or dependent variable, should be a string.
n_fold	the number of folds to use for doing kfold computation, default=5
seed	the seed value, to ensure reproducibility, it could be any positive value, default=42

Value

a train and test data table with out-of-fold mean value of the target for the given categorical variable

Examples

```
train <- data.frame(region=c('del','csk','rcb','del','csk','pune','guj','del'),
                    win = c(0,1,1,0,0,0,0,1))
test <- data.frame(region=c('rcb','csk','rcb','del','guj','pune','csk','kol'))
train_result <- kFoldMean(train_df = train,
                          test_df = test,
                          colname = 'region',
                          target = 'win',
                          seed = 1220)$train

test_result <- kFoldMean(train_df = train,
                         test_df = test,
                         colname = 'region',
                         target = 'win',
                         seed = 1220)$test
```

KMeansTrainer

K-Means Trainer

Description

Trains a k-means machine learning model in R

Details

Trains a unsupervised K-Means clustering algorithm. It borrows mini-batch k-means function from ClusterR package written in c++, hence it is quite fast.

Public fields

`clusters` the number of clusters

`batch_size` the size of the mini batches

`num_init` number of times the algorithm will be run with different centroid seeds

`max_iters` the maximum number of clustering iterations

`init_fraction` percentage of data to use for the initialization centroids (applies if initializer is `kmeans++` or `optimal_init`). Should be a float number between 0.0 and 1.0.

`initializer` the method of initialization. One of, `optimal_init`, `quantile_init`, `kmeans++` and `random`.

`early_stop_iter` continue that many iterations after calculation of the best within-cluster-sum-ofsquared-error

`verbose` either TRUE or FALSE, indicating whether progress is printed during clustering

`centroids` a matrix of initial cluster centroids. The rows of the CENTROIDS matrix should be equal to the number of clusters and the columns should be equal to the columns of the data

`tol` a float number. If, in case of an iteration (`iteration > 1` and `iteration < max_iters`) "`tol`" is greater than the squared norm of the centroids, then `kmeans` has converged

`tol_optimal_init` tolerance value for the '`optimal_init`' initializer. The higher this value is, the far apart from each other the centroids are.

`seed` integer value for random number generator (RNG)

`model` use for internal purpose

`max_clusters` either a numeric value, a contiguous or non-contiguous numeric vector specifying the cluster search space

Methods

Public methods:

- [KMeansTrainer\\$new\(\)](#)
- [KMeansTrainer\\$fit\(\)](#)
- [KMeansTrainer\\$predict\(\)](#)

- [KMeansTrainer\\$clone\(\)](#)

Method new():

Usage:

```
KMeansTrainer$new(
  clusters,
  batch_size = 10,
  num_init = 1,
  max_iters = 100,
  init_fraction = 1,
  initializer = "kmeans++",
  early_stop_iter = 10,
  verbose = FALSE,
  centroids = NULL,
  tol = 1e-04,
  tol_optimal_init = 0.3,
  seed = 1,
  max_clusters = NA
)
```

Arguments:

`clusters` numeric, When building the vocabulary ignore terms that have a document frequency strictly lower than the given threshold, value lies between 0 and 1.

`batch_size` numeric, When building the vocabulary ignore terms that have a document frequency strictly higher than the given threshold, value lies between 0 and 1.

`num_init` integer, use top features sorted by count to be used in bag of words matrix.

`max_iters` character, regex expression to use for text cleaning.

`init_fraction` list, a list of stopwords to use, by default it uses its inbuilt list of standard stopwords

`initializer` character, splitting criteria for strings, default: " "

`early_stop_iter` continue that many iterations after calculation of the best within-cluster-sum-of-squared-error

`verbose` either TRUE or FALSE, indicating whether progress is printed during clustering

`centroids` a matrix of initial cluster centroids. The rows of the CENTROIDS matrix should be equal to the number of clusters and the columns should be equal to the columns of the data

`tol` a float number. If, in case of an iteration (iteration > 1 and iteration < max_iters) "tol" is greater than the squared norm of the centroids, then kmeans has converged

`tol_optimal_init` tolerance value for the 'optimal_init' initializer. The higher this value is, the far apart from each other the centroids are.

`seed` integer value for random number generator (RNG)

`max_clusters` either a numeric value, a contiguous or non-contiguous numeric vector specifying the cluster search space

Details: Create a new 'KMeansTrainer' object.

Returns: A 'KMeansTrainer' object.

Examples:

```
data <- rbind(replicate(20, rnorm(1e4, 2)),
             replicate(20, rnorm(1e4, -1)),
             replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)
```

Method fit():

Usage:

```
KMeansTrainer$fit(X, y = NULL, find_optimal = FALSE)
```

Arguments:

X data.frame or matrix containing features

y NULL only kept here for superml's standard way

find_optimal logical, to find the optimal clusters automatically

Details: Trains the KMeansTrainer model

Returns: NULL

Examples:

```
data <- rbind(replicate(20, rnorm(1e4, 2)),
             replicate(20, rnorm(1e4, -1)),
             replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)
km_model$fit(data, find_optimal = FALSE)
```

Method predict():

Usage:

```
KMeansTrainer$predict(X)
```

Arguments:

X data.frame or matrix

Details: Returns the prediction on test data

Returns: a vector of predictions

Examples:

```
data <- rbind(replicate(20, rnorm(1e4, 2)),
             replicate(20, rnorm(1e4, -1)),
             replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)
km_model$fit(data, find_optimal = FALSE)
predictions <- km_model$predict(data)
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
KMeansTrainer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `KMeansTrainer$new`
## -----

data <- rbind(replicate(20, rnorm(1e4, 2)),
              replicate(20, rnorm(1e4, -1)),
              replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)

## -----
## Method `KMeansTrainer$fit`
## -----

data <- rbind(replicate(20, rnorm(1e4, 2)),
              replicate(20, rnorm(1e4, -1)),
              replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)
km_model$fit(data, find_optimal = FALSE)

## -----
## Method `KMeansTrainer$predict`
## -----

data <- rbind(replicate(20, rnorm(1e4, 2)),
              replicate(20, rnorm(1e4, -1)),
              replicate(20, rnorm(1e4, 5)))
km_model <- KMeansTrainer$new(clusters=2, batch_size=30, max_clusters=6)
km_model$fit(data, find_optimal = FALSE)
predictions <- km_model$predict(data)
```

KNNTrainer

K Nearest Neighbours Trainer

Description

Trains a k nearest neighbour model using fast search algorithms. KNN is a supervised learning algorithm which is used for both regression and classification problems.

Format

[R6Class](#) object.

Usage

For usage details see **Methods, Arguments and Examples** sections.

```
bst = KNNTrainer$new(k=1, prob=FALSE, algorithm=NULL, type="class")
bst$fit(X_train, X_test, "target")
bst$predict(type)
```

Methods

`$new()` Initialise the instance of the trainer
`$fit()` trains the knn model and stores the test prediction
`$predict()` returns predictions

Arguments

k number of neighbours to predict
prob if probability should be computed, default=FALSE
algorithm algorithm used to train the model, possible values are 'kd_tree', 'cover_tree', 'brute'
type type of problem to solve i.e. regression or classification, possible values are 'reg' or 'class'

Public fields

k number of neighbours to predict
prob if probability should be computed, default=FALSE
algorithm algorithm used to train the model, possible values are 'kd_tree', 'cover_tree', 'brute'
type type of problem to solve i.e. regression or classification, possible values are 'reg' or 'class'
model for internal use

Methods**Public methods:**

- `KNNTrainer$new()`
- `KNNTrainer$fit()`
- `KNNTrainer$predict()`
- `KNNTrainer$clone()`

Method new():

Usage:

`KNNTrainer$new(k, prob, algorithm, type)`

Arguments:

k k number of neighbours to predict
prob if probability should be computed, default=FALSE
algorithm algorithm used to train the model, possible values are 'kd_tree', 'cover_tree', 'brute'
type type of problem to solve i.e. regression or classification, possible values are 'reg' or 'class'

Details: Create a new 'KNNTrainer' object.

Returns: A 'KNNTrainer' object.

Examples:

```

data("iris")

iris$Species <- as.integer(as.factor(iris$Species))

xtrain <- iris[1:100,]
xtest <- iris[101:150,]

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')
pred <- bst$predict(type="raw")

```

Method fit():*Usage:*

```
KNNTrainer$fit(train, test, y)
```

Arguments:

train data.frame or matrix

test data.frame or matrix

y character, name of target variable

Details: Trains the KNNTrainer model*Returns:* NULL*Examples:*

```
data("iris")
```

```
iris$Species <- as.integer(as.factor(iris$Species))
```

```
xtrain <- iris[1:100,]
```

```
xtest <- iris[101:150,]
```

```
bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
```

```
bst$fit(xtrain, xtest, 'Species')
```

Method predict():*Usage:*

```
KNNTrainer$predict(type = "raw")
```

Arguments:

type character, 'raw' for labels else 'prob'

Details: Predicts the nearest neighbours for test data*Returns:* a list of predicted neighbours*Examples:*

```
data("iris")
```

```
iris$Species <- as.integer(as.factor(iris$Species))
```

```
xtrain <- iris[1:100,]
```

```
xtest <- iris[101:150,]

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')
pred <- bst$predict(type="raw")
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
KNNTrainer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
data("iris")

iris$Species <- as.integer(as.factor(iris$Species))

xtrain <- iris[1:100,]
xtest <- iris[101:150,]

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')
pred <- bst$predict(type="raw")

## -----
## Method `KNNTrainer$new`
## -----

data("iris")

iris$Species <- as.integer(as.factor(iris$Species))

xtrain <- iris[1:100,]
xtest <- iris[101:150,]

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')
pred <- bst$predict(type="raw")

## -----
## Method `KNNTrainer$fit`
## -----

data("iris")

iris$Species <- as.integer(as.factor(iris$Species))

xtrain <- iris[1:100,]
xtest <- iris[101:150,]
```

```

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')

## -----
## Method `KNNTrainer$predict`
## -----

data("iris")

iris$Species <- as.integer(as.factor(iris$Species))

xtrain <- iris[1:100,]
xtest <- iris[101:150,]

bst <- KNNTrainer$new(k=3, prob=TRUE, type="class")
bst$fit(xtrain, xtest, 'Species')
pred <- bst$predict(type="raw")

```

LabelEncoder

Label Encoder

Description

Encodes and decodes categorical variables into integer values and vice versa. This is a commonly performed task in data preparation during model training, because all machine learning models require the data to be encoded into numerical format. It takes a vector of character or factor values and encodes them into numeric.

Format

[R6Class](#) object.

Usage

For usage details see **Methods, Arguments and Examples** sections.

```

lbl = LabelEncoder$new()
lbl$fit(x)
lbl$fit_transform(x)
lbl$transform(x)

```

Methods

`$new()` Initialise the instance of the encoder
`$fit()` creates a memory of encodings but doesn't return anything
`$transform()` based on encodings learned in fit method is applies the transformation
`$fit_transform()` encodes the data and keep a memory of encodings simultaneously
`$inverse_transform()` encodes the data and keep a memory of encodings simultaneously

Arguments

data a vector or list containing the character / factor values

Public fields

input_data internal use

encodings internal use

decodings internal use

fit_model internal use

Methods**Public methods:**

- [LabelEncoder\\$fit\(\)](#)
- [LabelEncoder\\$fit_transform\(\)](#)
- [LabelEncoder\\$transform\(\)](#)
- [LabelEncoder\\$inverse_transform\(\)](#)
- [LabelEncoder\\$clone\(\)](#)

Method fit():

Usage:

```
LabelEncoder$fit(data_col)
```

Arguments:

data_col a vector containing non-null values

Details: Fits the labelencoder model on given data

Returns: NULL, calculates the encoding and save in memory

Examples:

```
data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao', 'Bo', 'Bo', 'Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)
decode_names <- lbl$inverse_transform(data_ex$Name)
```

Method fit_transform():

Usage:

```
LabelEncoder$fit_transform(data_col)
```

Arguments:

data_col a vector containing non-null values

Details: Fits and returns the encoding

Returns: encoding values for the given input data

Examples:

```
data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao', 'Bo', 'Bo', 'Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)
```

Method transform():*Usage:*

```
LabelEncoder$transform(data_col)
```

Arguments:

data_col a vector containing non-null values

Details: Returns the encodings from the fitted model

Returns: encoding values for the given input data

Examples:

```
data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao', 'Bo', 'Bo', 'Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$transform(data_ex$Name)
```

Method inverse_transform():*Usage:*

```
LabelEncoder$inverse_transform(coded_col)
```

Arguments:

coded_col a vector containing label encoded values

Details: Gives back the original values from a encoded values

Returns: original values from the label encoded data

Examples:

```
data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao', 'Bo', 'Bo', 'Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)
decode_names <- lbl$inverse_transform(data_ex$Name)
```

Method clone(): The objects of this class are cloneable with this method.*Usage:*

```
LabelEncoder$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao', 'Bo', 'Bo', 'Co'))
lbl <- LabelEncoder$new()
data_ex$Name <- lbl$fit_transform(data_ex$Name)
decode_names <- lbl$inverse_transform(data_ex$Name)
```

```

## -----
## Method `LabelEncoder$fit`
## -----

data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao','Bo','Bo','Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)
decode_names <- lbl$inverse_transform(data_ex$Name)

## -----
## Method `LabelEncoder$fit_transform`
## -----

data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao','Bo','Bo','Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)

## -----
## Method `LabelEncoder$transform`
## -----

data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao','Bo','Bo','Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$transform(data_ex$Name)

## -----
## Method `LabelEncoder$inverse_transform`
## -----

data_ex <- data.frame(Score = c(10,20,30,4), Name=c('Ao','Bo','Bo','Co'))
lbl <- LabelEncoder$new()
lbl$fit(data_ex$Name)
data_ex$Name <- lbl$fit_transform(data_ex$Name)
decode_names <- lbl$inverse_transform(data_ex$Name)

```

Description

Trains regression, lasso, ridge model in R

Details

Trains linear models such as Logistic, Lasso or Ridge regression model. It is built on glmnet R package. This class provides fit, predict, cross validation functions.

Public fields

family type of regression to perform, values can be "gaussian", "binomial", "multinomial", "mgaussian"
 weights observation weights. Can be total counts if responses are proportion matrices. Default is 1 for each observation
 alpha The elasticnet mixing parameter, alpha=1 is the lasso penalty, alpha=0 the ridge penalty, alpha=NULL is simple regression
 lambda the number of lambda values - default is 100
 standardize normalise the features in the given data
 standardize.response normalise the dependent variable between 0 and 1, default = FALSE
 model internal use
 cvmodel internal use
 Flag internal use
 is_lasso internal use
 iid_names internal use

Methods**Public methods:**

- [LMTrainer\\$new\(\)](#)
- [LMTrainer\\$fit\(\)](#)
- [LMTrainer\\$predict\(\)](#)
- [LMTrainer\\$cv_model\(\)](#)
- [LMTrainer\\$cv_predict\(\)](#)
- [LMTrainer\\$get_importance\(\)](#)
- [LMTrainer\\$clone\(\)](#)

Method new():*Usage:*

```
LMTrainer$new(family, weights, alpha, lambda, standardize.response)
```

Arguments:

family character, type of regression to perform, values can be "gaussian", "binomial", "multinomial", "mgaussian"
 weights numeric, observation weights. Can be total counts if responses are proportion matrices. Default is 1 for each observation
 alpha integer, The elasticnet mixing parameter, alpha=1 is the lasso penalty, alpha=0 the ridge penalty, alpha=NULL is simple regression
 lambda integer, the number of lambda values - default is 100
 standardize.response logical, normalise the dependent variable between 0 and 1, default = FALSE

Details: Create a new 'LMTrainer' object.

Returns: A 'LMTrainer' object.

Examples:

```
\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
          "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
}
```

Method fit():*Usage:*

```
LMTrainer$fit(X, y)
```

Arguments:

X data.frame containing train features
y character, name of target variable

Details: Fits the LMTrainer model on given data

Returns: NULL, train the model and saves internally

Examples:

```
\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
          "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$fit(X = housing, y = 'MEDV')
}
```

Method predict():*Usage:*

```
LMTrainer$predict(df, lambda = NULL)
```

Arguments:

df data.frame containing test features
lambda integer, the number of lambda values - default is 100. By default it picks the best value from the model.

Details: Returns predictions for test data

Returns: vector, a vector containing predictions

Examples:

```
\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
```

```

      "RAD", "TAX", "PTRATIO", "B", "LSTAT", "MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$fit(X = housing, y = 'MEDV')
predictions <- lf$cv_predict(df = housing)
}

```

Method `cv_model()`:

Usage:

```
LMTrainer$cv_model(X, y, nfolds, parallel, type.measure = "deviance")
```

Arguments:

X data.frame containing test features

y character, name of target variable

nfolds integer, number of folds

parallel logical, if do parallel computation. Default=FALSE

type.measure character, evaluation metric type. Default = deviance

Details: Train regression model using cross validation

Returns: NULL, trains the model and saves it in memory

Examples:

```

\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM", "ZN", "INDUS", "CHAS", "NOX", "RM", "AGE", "DIS",
          "RAD", "TAX", "PTRATIO", "B", "LSTAT", "MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfolds = 5, parallel = FALSE)
}

```

Method `cv_predict()`:

Usage:

```
LMTrainer$cv_predict(df, lambda = NULL)
```

Arguments:

df data.frame containing test features

lambda integer, the number of lambda values - default is 100. By default it picks the best value from the model.

Details: Get predictions from the cross validated regression model

Returns: vector a vector containing predicted values

Examples:

```

\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM", "ZN", "INDUS", "CHAS", "NOX", "RM", "AGE", "DIS",

```

```

      "RAD", "TAX", "PTRATIO", "B", "LSTAT", "MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfolds = 5, parallel = FALSE)
predictions <- lf$cv_predict(df = housing)
}

```

Method get_importance():*Usage:*

LMTrainer\$get_importance()

Details: Get feature importance using model coefficients*Returns:* a matrix containing feature coefficients*Examples:*

```

\dontrun{
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM", "ZN", "INDUS", "CHAS", "NOX", "RM", "AGE", "DIS",
          "RAD", "TAX", "PTRATIO", "B", "LSTAT", "MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfolds = 5, parallel = FALSE)
predictions <- lf$cv_predict(df = housing)
coefs <- lf$get_importance()
}

```

Method clone(): The objects of this class are cloneable with this method.*Usage:*

LMTrainer\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Examples

```

## -----
## Method `LMTrainer$new`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM", "ZN", "INDUS", "CHAS", "NOX", "RM", "AGE", "DIS",
          "RAD", "TAX", "PTRATIO", "B", "LSTAT", "MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)

## End(Not run)

```

```

## -----
## Method `LMTrainer$fit`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
           "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$fit(X = housing, y = 'MEDV')

## End(Not run)

## -----
## Method `LMTrainer$predict`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
           "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$fit(X = housing, y = 'MEDV')
predictions <- lf$cv_predict(df = housing)

## End(Not run)

## -----
## Method `LMTrainer$cv_model`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
           "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfold = 5, parallel = FALSE)

## End(Not run)

## -----
## Method `LMTrainer$cv_predict`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)

```

```

names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
           "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfolds = 5, parallel = FALSE)
predictions <- lf$cv_predict(df = housing)

## End(Not run)

## -----
## Method `LMTrainer$get_importance`
## -----

## Not run:
LINK <- "http://archive.ics.uci.edu/ml/machine-learning-databases/housing/housing.data"
housing <- read.table(LINK)
names <- c("CRIM","ZN","INDUS","CHAS","NOX","RM","AGE","DIS",
           "RAD","TAX","PTRATIO","B","LSTAT","MEDV")
names(housing) <- names
lf <- LMTrainer$new(family = 'gaussian', alpha=1)
lf$cv_model(X = housing, y = 'MEDV', nfolds = 5, parallel = FALSE)
predictions <- lf$cv_predict(df = housing)
coefs <- lf$get_importance()

## End(Not run)

```

NBTrainer

Naive Bayes Trainer

Description

Trains a probabilistic naive bayes model

Details

Trains a naive bayes model. It is built on top high performance naivebayes R package.

Public fields

`prior` numeric vector with prior probabilities. `vector` vector with prior probabilities of the classes. If unspecified, the class proportions for the training set are used. If present, the probabilities should be specified in the order of the factor levels.

`laplace` value used for Laplace smoothing. Defaults to 0 (no Laplace smoothing)

`usekernel` if TRUE, density is used to estimate the densities of metric predictors

`model` for internal use

Methods

Public methods:

- `NBTrainer$new()`
- `NBTrainer$fit()`
- `NBTrainer$predict()`
- `NBTrainer$clone()`

Method `new()`:

Usage:

```
NBTrainer$new(prior, laplace, usekernel)
```

Arguments:

`prior` numeric, prior numeric vector with prior probabilities. vector with prior probabilities of the classes. If unspecified, the class proportions for the training set are used. If present, the probabilities should be specified in the order of the factor levels.

`laplace` numeric, value used for Laplace smoothing. Defaults to 0 (no Laplace smoothing)

`usekernel` logical, if TRUE, density is used to estimate the densities of metric predictors

Details: Create a new 'NBTrainer' object.

Returns: A 'NBTrainer' object.

Examples:

```
data(iris)
nb <- NBTrainer$new()
```

Method `fit()`:

Usage:

```
NBTrainer$fit(X, y)
```

Arguments:

`X` data.frame containing train features

`y` character, name of target variable

Details: Fits the naive bayes model

Returns: NULL, trains and saves the model in memory

Examples:

```
data(iris)
nb <- NBTrainer$new()
nb$fit(iris, 'Species')
```

Method `predict()`:

Usage:

```
NBTrainer$predict(X, type = "class")
```

Arguments:

`X` data.frame containing test features

`type` character, if the predictions should be labels or probability

Details: Returns predictions from the model

Returns: NULL, trains and saves the model in memory

Examples:

```
data(iris)
nb <- NBTrainer$new()
nb$fit(iris, 'Species')
y <- nb$predict(iris)
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
NBTrainer$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `NBTrainer$new`
## -----

data(iris)
nb <- NBTrainer$new()

## -----
## Method `NBTrainer$fit`
## -----

data(iris)
nb <- NBTrainer$new()
nb$fit(iris, 'Species')

## -----
## Method `NBTrainer$predict`
## -----

data(iris)
nb <- NBTrainer$new()
nb$fit(iris, 'Species')
y <- nb$predict(iris)
```

normalise1d

normalise1d

Description

Normalises a 1 dimensional vector towards unit p norm. By default, $p = 2$ is used. For a given vector, eg: $c(1,2,3)$, norm value is calculated as $'x / |x|'$ where $'|x|'$ is calculated as the square root of sum of square of values in the given vector.

Usage

```
normalise1d(vec, pnorm = 2L)
```

Arguments

vec	vector containing integers or numeric values.
pnorm	integer, default: 2

Value

a vector containing normalised values

Examples

```
val <- c(1,10,5,3,8)
norm_val <- normalise1d(val)
```

normalise2d	<i>normalise2d</i>
-------------	--------------------

Description

Normalises a matrix towards unit p norm row wise or column wise. By default, p = 2 is used. To normalise row wise, use axis=0. To normalise column wise, use axis=1. as the square root of sum of square of values in the given vector.

Usage

```
normalise2d(mat, pnorm = 2L, axis = 1L)
```

Arguments

mat	numeric matrix
pnorm	integer value, default value=2
axis	integer (0 or 1), row wise = 0, column wise = 1

Value

normalised numeric matrix

Examples

```
mat <- matrix(runif(12), 3, 4)

## normalise matrix row wise
r <- normalise2d(mat, axis=0)

## normalise matrix column wise
r <- normalise2d(mat, axis=1)
```

RandomSearchCV

Random Search CV

Description

Hyperparameter tuning using random search scheme.

Details

Given a set of hyper parameters, random search trainer provides a faster way of hyper parameter tuning. Here, the number of models to be trained can be defined by the user.

Super class

`superml::GridSearchCV` -> `RandomSearchTrainer`

Public fields

`n_iter` number of models to be trained

Methods

Public methods:

- `RandomSearchCV$new()`
- `RandomSearchCV$fit()`
- `RandomSearchCV$clone()`

Method `new()`:

Usage:

```
RandomSearchCV$new(  
  trainer = NA,  
  parameters = NA,  
  n_folds = NA,  
  scoring = NA,  
  n_iter = NA  
)
```

Arguments:

trainer superml trainer object, must be either XGBTrainer, LMTrainer, RFTrainer, NBTrainer
parameters list, list containing parameters
n_folds integer, number of folds to use to split the train data
scoring character, scoring metric used to evaluate the best model, multiple values can be provided. currently supports: auc, accuracy, mse, rmse, logloss, mae, f1, precision, recall
n_iter integer, number of models to be trained

Details: Create a new 'RandomSearchTrainer' object.

Returns: A 'RandomSearchTrainer' object.

Examples:

```
rf <- RFTrainer$new()
rst <- RandomSearchCV$new(trainer = rf,
                          parameters = list(n_estimators = c(100,500),
                                             max_depth = c(5,2,10,14)),
                          n_folds = 3,
                          scoring = c('accuracy', 'auc'),
                          n_iter = 4)
```

Method fit():

Usage:

```
RandomSearchCV$fit(X, y)
```

Arguments:

X data.frame containing features
y character, name of target variable

Details: Train the model on given hyperparameters

Returns: NULL, tunes hyperparameters and stores the result in memory

Examples:

```
rf <- RFTrainer$new()
rst <- RandomSearchCV$new(trainer = rf,
                          parameters = list(n_estimators = c(100,500),
                                             max_depth = c(5,2,10,14)),
                          n_folds = 3,
                          scoring = c('accuracy', 'auc'),
                          n_iter = 4)

data("iris")
rst$fit(iris, "Species")
rst$best_iteration()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
RandomSearchCV$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `RandomSearchCV$new`
## -----

rf <- RFTrainer$new()
rst <- RandomSearchCV$new(trainer = rf,
                          parameters = list(n_estimators = c(100,500),
                                             max_depth = c(5,2,10,14)),
                          n_folds = 3,
                          scoring = c('accuracy','auc'),
                          n_iter = 4)

## -----
## Method `RandomSearchCV$fit`
## -----

rf <- RFTrainer$new()
rst <- RandomSearchCV$new(trainer = rf,
                          parameters = list(n_estimators = c(100,500),
                                             max_depth = c(5,2,10,14)),
                          n_folds = 3,
                          scoring = c('accuracy','auc'),
                          n_iter = 4)

data("iris")
rst$fit(iris, "Species")
rst$best_iteration()
```

*reg_train**reg_train*

Description

Training Dataset used for regression examples. In this data set, we have to predict the sale price of the houses.

Usage

```
reg_train
```

Format

An object of class `data.table` (inherits from `data.frame`) with 1460 rows and 81 columns.

Source

<https://www.kaggle.com/c/house-prices-advanced-regression-techniques/data>

RFTrainer

*Random Forest Trainer***Description**

Trains a random forest model.

Details

Trains a Random Forest model. A random forest is a meta estimator that fits a number of decision tree classifiers on various sub-samples of the dataset and use averaging to improve the predictive accuracy and control over-fitting. This implementation uses ranger R package which provides faster model training.

Public fields

`n_estimators` the number of trees in the forest, default= 100

`max_features` the number of features to consider when looking for the best split. Possible values are `auto`(default) takes `sqrt(num_of_features)`, `sqrt` same as `auto`, `log` takes `log(num_of_features)`, `none` takes all features

`max_depth` the maximum depth of each tree

`min_node_size` the mininum number of samples required to split an internal node

`criterion` the function to measure the quality of split. For classification, `gini` is used which is a measure of gini index. For regression, the variance of responses is used.

`classification` whether to train for classification (1) or regression (0)

`verbose` show computation status and estimated runtime

`seed` seed value

`class_weights` weights associated with the classes for sampling of training observation

`always_split` vector of feature names to be always used for splitting

`importance` Variable importance mode, one of 'none', 'impurity', 'impurity_corrected', 'permutation'. The 'impurity' measure is the Gini index for classification, the variance of the responses for regression. Defaults to "impurity"

Methods**Public methods:**

- `RFTrainer$new()`
- `RFTrainer$fit()`
- `RFTrainer$predict()`
- `RFTrainer$get_importance()`
- `RFTrainer$clone()`

Method `new()`:

Usage:

```
RFTrainer$new(
  n_estimators,
  max_depth,
  max_features,
  min_node_size,
  classification,
  class_weights,
  always_split,
  verbose,
  save_model,
  seed,
  importance
)
```

Arguments:

`n_estimators` integer, the number of trees in the forest, default= 100

`max_depth` integer, the maximum depth of each tree

`max_features` integer, the number of features to consider when looking for the best split. Possible values are `auto`(default) takes $\sqrt{\text{num_of_features}}$, `sqrt` same as `auto`, `log` takes $\log(\text{num_of_features})$, `none` takes all features

`min_node_size` integer, the minimum number of samples required to split an internal node

`classification` integer, whether to train for classification (1) or regression (0)

`class_weights` weights associated with the classes for sampling of training observation

`always_split` vector of feature names to be always used for splitting

`verbose` logical, show computation status and estimated runtime

`save_model` logical, whether to save model

`seed` integer, seed value

`importance` Variable importance mode, one of 'none', 'impurity', 'impurity_corrected', 'permutation'. The 'impurity' measure is the Gini index for classification, the variance of the responses for regression. Defaults to "impurity"

Details: Create a new 'RFTrainer' object.

Returns: A 'RFTrainer' object.

Examples:

```
data("iris")
bst <- RFTrainer$new(n_estimators=10,
                    max_depth=4,
                    classification=1,
                    seed=42,
                    verbose=TRUE)
```

Method fit():*Usage:*

```
RFTrainer$fit(X, y)
```

Arguments:

X data.frame containing train features
y character, name of the target variable
Details: Trains the random forest model
Returns: NULL, trains and saves the model in memory
Examples:
data("iris")
bst <- RFTrainer\$new(n_estimators=10,
 max_depth=4,
 classification=1,
 seed=42,
 verbose=TRUE)
bst\$fit(iris, 'Species')

Method predict():

Usage:
RFTrainer\$predict(df)
Arguments:
df data.frame containing test features
Details: Return predictions from random forest model
Returns: a vector containing predictions
Examples:
data("iris")
bst <- RFTrainer\$new(n_estimators=10,
 max_depth=4,
 classification=1,
 seed=42,
 verbose=TRUE)
bst\$fit(iris, 'Species')
predictions <- bst\$predict(iris)

Method get_importance():

Usage:
RFTrainer\$get_importance()
Details: Returns feature importance from the model
Returns: a data frame containing feature predictions
Examples:
data("iris")
bst <- RFTrainer\$new(n_estimators=50,
 max_depth=4,
 classification=1,
 seed=42,
 verbose=TRUE)
bst\$fit(iris, 'Species')
predictions <- bst\$predict(iris)
bst\$get_importance()

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
RFTrainer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `RFTrainer$new`
## -----

data("iris")
bst <- RFTrainer$new(n_estimators=10,
                    max_depth=4,
                    classification=1,
                    seed=42,
                    verbose=TRUE)

## -----
## Method `RFTrainer$fit`
## -----

data("iris")
bst <- RFTrainer$new(n_estimators=10,
                    max_depth=4,
                    classification=1,
                    seed=42,
                    verbose=TRUE)
bst$fit(iris, 'Species')

## -----
## Method `RFTrainer$predict`
## -----

data("iris")
bst <- RFTrainer$new(n_estimators=10,
                    max_depth=4,
                    classification=1,
                    seed=42,
                    verbose=TRUE)
bst$fit(iris, 'Species')
predictions <- bst$predict(iris)

## -----
## Method `RFTrainer$get_importance`
## -----

data("iris")
bst <- RFTrainer$new(n_estimators=50,
                    max_depth=4,
```

```
classification=1,  
seed=42,  
verbose=TRUE)  
bst$fit(iris, 'Species')  
predictions <- bst$predict(iris)  
bst$get_importance()
```

smoothMean

smoothMean Calculator

Description

Calculates target encodings using a smoothing parameter and count of categorical variables. This approach is more robust to possibility of leakage and avoid overfitting.

Usage

```
smoothMean(  
  train_df,  
  test_df,  
  colname,  
  target,  
  min_samples_leaf = 1,  
  smoothing = 1,  
  noise_level = 0  
)
```

Arguments

train_df	train dataset
test_df	test dataset
colname	name of categorical column
target	name of target column
min_samples_leaf	minimum samples to take category average into account
smoothing	smoothing effect to balance categorical average vs prior
noise_level	random noise to add, optional

Value

a train and test data table with mean encodings of the target for the given categorical variable

Examples

```
train <- data.frame(region=c('del','csk','rcb','del','csk','pune','guj','del'),
                    win = c(0,1,1,0,0,1,0,1))
test <- data.frame(region=c('rcb','csk','rcb','del','guj','pune','csk','kol'))

# calculate encodings
all_means <- smoothMean(train_df = train,
                        test_df = test,
                        colname = 'region',
                        target = 'win')
train_mean <- all_means$train
test_mean <- all_means$test
```

sort_index

sort_index

Description

For a given vector, return the indexes of the sorted array and not the sorted array itself.

Usage

```
sort_index(vec, ascending = TRUE)
```

Arguments

vec	numeric vector
ascending	logical, order to return (ascending or descending), default = True

Value

numeric vector containing sorted indexes

Examples

```
v <- c(10,3,1,4)
j <- sort_index(v)
```

TfidfVectorizer

TfIDF(Term Frequency Inverse Document Frequency) Vectorizer

Description

Creates a tf-idf matrix

Details

Given a list of text, it creates a sparse matrix consisting of tf-idf score for tokens from the text.

Super class

`superml:CountVectorizer` -> TfidfVectorizer

Public fields

`sentences` a list containing sentences

`max_df` When building the vocabulary ignore terms that have a document frequency strictly higher than the given threshold, value lies between 0 and 1.

`min_df` When building the vocabulary ignore terms that have a document frequency strictly lower than the given threshold, value lies between 0 and 1.

`max_features` use top features sorted by count to be used in bag of words matrix.

`ngram_range` The lower and upper boundary of the range of n-values for different word n-grams or char n-grams to be extracted. All values of n such such that $\text{min_n} \leq n \leq \text{max_n}$ will be used. For example an `ngram_range` of `c(1, 1)` means only unigrams, `c(1, 2)` means unigrams and bigrams, and `c(2, 2)` means only bigrams.

`split` splitting criteria for strings, default: " "

`lowercase` convert all characters to lowercase before tokenizing

`regex` regex expression to use for text cleaning.

`remove_stopwords` a list of stopwords to use, by default it uses its inbuilt list of standard stopwords

`smooth_idf` logical, to prevent zero division, adds one to document frequencies, as if an extra document was seen containing every term in the collection exactly once

`norm` logical, if TRUE, each output row will have unit norm 'l2': Sum of squares of vector elements is 1. if FALSE returns non-normalized vectors, default: TRUE

Methods

Public methods:

- `TfidfVectorizer$new()`
- `TfidfVectorizer$fit()`
- `TfidfVectorizer$fit_transform()`
- `TfidfVectorizer$transform()`

- [TfidfVectorizer\\$clone\(\)](#)

Method `new()`:

Usage:

```
TfidfVectorizer$new(
  min_df,
  max_df,
  max_features,
  ngram_range,
  regex,
  remove_stopwords,
  split,
  lowercase,
  smooth_idf,
  norm
)
```

Arguments:

`min_df` numeric, When building the vocabulary ignore terms that have a document frequency strictly lower than the given threshold, value lies between 0 and 1.

`max_df` numeric, When building the vocabulary ignore terms that have a document frequency strictly higher than the given threshold, value lies between 0 and 1.

`max_features` integer, Build a vocabulary that only consider the top `max_features` ordered by term frequency across the corpus.

`ngram_range` vector, The lower and upper boundary of the range of n-values for different word n-grams or char n-grams to be extracted. All values of n such such that `min_n <= n <= max_n` will be used. For example an `ngram_range` of `c(1, 1)` means only unigrams, `c(1, 2)` means unigrams and bigrams, and `c(2, 2)` means only bigrams.

`regex` character, regex expression to use for text cleaning.

`remove_stopwords` list, a list of stopwords to use, by default it uses its inbuilt list of standard english stopwords

`split` character, splitting criteria for strings, default: " "

`lowercase` logical, convert all characters to lowercase before tokenizing, default: TRUE

`smooth_idf` logical, to prevent zero division, adds one to document frequencies, as if an extra document was seen containing every term in the collection exactly once

`norm` logical, if TRUE, each output row will have unit norm 'l2': Sum of squares of vector elements is 1. if FALSE returns non-normalized vectors, default: TRUE

`parallel` logical, speeds up ngrams computation using n-1 cores, defaults: TRUE

Details: Create a new 'TfidfVectorizer' object.

Returns: A 'TfidfVectorizer' object.

Examples:

```
TfidfVectorizer$new()
```

Method `fit()`:

Usage:

```
TfidfVectorizer$fit(sentences)
```

Arguments:

sentences a list of text sentences

Details: Fits the TfIdfVectorizer model on sentences

Returns: NULL

Examples:

```
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
tf = TfIdfVectorizer$new(smooth_idf = TRUE, min_df = 0.3)
tf$fit(sents)
```

Method fit_transform():*Usage:*

```
TfIdfVectorizer$fit_transform(sentences)
```

Arguments:

sentences a list of text sentences

Details: Fits the TfIdfVectorizer model and returns a sparse matrix of count of tokens

Returns: a sparse matrix containing tf-idf score for tokens in each given sentence

Examples:

```
\dontrun{
sents <- c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
tf <- TfIdfVectorizer$new(smooth_idf = TRUE, min_df = 0.1)
tf_matrix <- tf$fit_transform(sents)
}
```

Method transform():*Usage:*

```
TfIdfVectorizer$transform(sentences)
```

Arguments:

sentences a list of new text sentences

Details: Returns a matrix of tf-idf score of tokens

Returns: a sparse matrix containing tf-idf score for tokens in each given sentence

Examples:

```
\dontrun{
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
new_sents <- c("dark at night", 'mothers day')
tf = TfIdfVectorizer$new(min_df=0.1)
tf$fit(sents)
tf_matrix <- tf$transform(new_sents)
}
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
TfIdfVectorizer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `TfIdfVectorizer$new`
## -----

TfIdfVectorizer$new()

## -----
## Method `TfIdfVectorizer$fit`
## -----

sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
tf = TfIdfVectorizer$new(smooth_idf = TRUE, min_df = 0.3)
tf$fit(sents)

## -----
## Method `TfIdfVectorizer$fit_transform`
## -----

## Not run:
sents <- c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
tf <- TfIdfVectorizer$new(smooth_idf = TRUE, min_df = 0.1)
tf_matrix <- tf$fit_transform(sents)

## End(Not run)

## -----
## Method `TfIdfVectorizer$transform`
## -----

## Not run:
sents = c('i am alone in dark.', 'mother_mary a lot',
          'alone in the dark?', 'many mothers in the lot...')
new_sents <- c("dark at night", 'mothers day')
tf = TfIdfVectorizer$new(min_df=0.1)
tf$fit(sents)
tf_matrix <- tf$transform(new_sents)

## End(Not run)
```

XGBTrainer

*Extreme Gradient Boosting Trainer***Description**

Trains a XGBoost model in R

Details

Trains a Extreme Gradient Boosting Model. XGBoost belongs to a family of boosting algorithms that creates an ensemble of weak learner to learn about data. It is a wrapper for original xgboost R package, you can find the documentation here: <http://xgboost.readthedocs.io/en/latest/parameter.html>

Public fields

`booster` the trainer type, the values are `gbtree(default)`, `gblinear`, `dart:gbtree`

`objective` specify the learning task. Check the link above for all possible values.

`nthread` number of parallel threads used to run, default is to run using all threads available

`silent` 0 means printing running messages, 1 means silent mode

`n_estimators` number of trees to grow, default = 100

`learning_rate` Step size shrinkage used in update to prevents overfitting. Lower the learning rate, more time it takes in training, value lies between between 0 and 1. Default = 0.3

`gamma` Minimum loss reduction required to make a further partition on a leaf node of the tree. The larger gamma is, the more conservative the algorithm will be. Value lies between 0 and infinity, Default = 0

`max_depth` the maximum depth of each tree, default = 6

`min_child_weight` Minimum sum of instance weight (hessian) needed in a child. If the tree partition step results in a leaf node with the sum of instance weight less than `min_child_weight`, then the building process will give up further partitioning. In linear regression task, this simply corresponds to minimum number of instances needed to be in each node. The larger `min_child_weight` is, the more conservative the algorithm will be. Value lies between 0 and infinity. Default = 1

`subsample` Subsample ratio of the training instances. Setting it to 0.5 means that XGBoost would randomly sample half of the training data prior to growing trees. and this will prevent overfitting. Subsampling will occur once in every boosting iteration. Value lies between 0 and 1. Default = 1

`colsample_bytree` Subsample ratio of columns when constructing each tree. Subsampling will occur once in every boosting iteration. Value lies between 0 and 1. Default = 1

`lambda` L2 regularization term on weights. Increasing this value will make model more conservative. Default = 1

`alpha` L1 regularization term on weights. Increasing this value will make model more conservative. Default = 0

`eval_metric` Evaluation metrics for validation data, a default metric will be assigned according to objective

`print_every` print training log after n iterations. Default = 50

`feval` custom evaluation function

`early_stopping` Used to prevent overfitting, stops model training after this number of iterations if there is no improvement seen

`maximize` If `feval` and `early_stopping_rounds` are set, then this parameter must be set as well. When it is TRUE, it means the larger the evaluation score the better.

`custom_objective` custom objective function

`save_period` when it is non-NULL, model is saved to disk after every `save_period` rounds, 0 means save at the end.

`save_name` the name or path for periodically saved model file.

`xgb_model` a previously built model to continue the training from. Could be either an object of class `xgb.Booster`, or its raw data, or the name of a file with a previously saved model.

`callbacks` a list of callback functions to perform various task during boosting. See `callbacks`. Some of the callbacks are automatically created depending on the parameters' values. User can provide either existing or their own callback methods in order to customize the training process.

`verbose` If 0, `xgboost` will stay silent. If 1, `xgboost` will print information of performance. If 2, `xgboost` will print some additional information. Setting `verbose > 0` automatically engages the `cb.evaluation.log` and `cb.print.evaluation` callback functions.

`watchlist` what information should be printed when `verbose=1` or `verbose=2`. Watchlist is used to specify validation set monitoring during training. For example user can specify `watchlist=list(validation1=mat1, validation2=mat2)` to watch the performance of each round's model on `mat1` and `mat2`

`num_class` set number of classes in case of multiclassification problem

`weight` a vector indicating the weight for each row of the input.

`na_missing` by default is set to NA, which means that NA values should be considered as 'missing' by the algorithm. Sometimes, 0 or other extreme value might be used to represent missing values. This parameter is only used when input is a dense matrix.

`feature_names` internal use, stores the feature names for model importance

`cv_model` internal use

Methods

Public methods:

- `XGBTrainer$new()`
- `XGBTrainer$cross_val()`
- `XGBTrainer$fit()`
- `XGBTrainer$predict()`
- `XGBTrainer$show_importance()`
- `XGBTrainer$clone()`

Method new():*Usage:*

```
XGBTrainer$new(
  booster,
  objective,
  nthread,
  silent,
  n_estimators,
  learning_rate,
  gamma,
  max_depth,
  min_child_weight,
  subsample,
  colsample_bytree,
  lambda,
  alpha,
  eval_metric,
  print_every,
  feval,
  early_stopping,
  maximize,
  custom_objective,
  save_period,
  save_name,
  xgb_model,
  callbacks,
  verbose,
  num_class,
  weight,
  na_missing
)
```

Arguments:

booster the trainer type, the values are gbtree(default), gblinear, dart:gbtree

objective specify the learning task. Check the link above for all possible values.

nthread number of parallel threads used to run, default is to run using all threads available

silent 0 means printing running messages, 1 means silent mode

n_estimators number of trees to grow, default = 100

learning_rate Step size shrinkage used in update to prevents overfitting. Lower the learning rate, more time it takes in training, value lies between between 0 and 1. Default = 0.3

gamma Minimum loss reduction required to make a further partition on a leaf node of the tree. The larger gamma is, the more conservative the algorithm will be. Value lies between 0 and infinity, Default = 0

max_depth the maximum depth of each tree, default = 6

min_child_weight Minimum sum of instance weight (hessian) needed in a child. If the tree partition step results in a leaf node with the sum of instance weight less than min_child_weight, then the building process will give up further partitioning. In linear regression task, this

- min_child_weight simply corresponds to minimum number of instances needed to be in each node. The larger min_child_weight is, the more conservative the algorithm will be. Value lies between 0 and infinity. Default = 1
- subsample Subsample ratio of the training instances. Setting it to 0.5 means that XGBoost would randomly sample half of the training data prior to growing trees, and this will prevent overfitting. Subsampling will occur once in every boosting iteration. Value lies between 0 and 1. Default = 1
- colsample_bytree Subsample ratio of columns when constructing each tree. Subsampling will occur once in every boosting iteration. Value lies between 0 and 1. Default = 1
- lambda L2 regularization term on weights. Increasing this value will make model more conservative. Default = 1
- alpha L1 regularization term on weights. Increasing this value will make model more conservative. Default = 0
- eval_metric Evaluation metrics for validation data, a default metric will be assigned according to objective
- print_every print training log after n iterations. Default = 50
- feval custom evaluation function
- early_stopping Used to prevent overfitting, stops model training after this number of iterations if there is no improvement seen
- maximize If feval and early_stopping_rounds are set, then this parameter must be set as well. When it is TRUE, it means the larger the evaluation score the better.
- custom_objective custom objective function
- save_period when it is non-NULL, model is saved to disk after every save_period rounds, 0 means save at the end.
- save_name the name or path for periodically saved model file.
- xgb_model a previously built model to continue the training from. Could be either an object of class xgb.Booster, or its raw data, or the name of a file with a previously saved model.
- callbacks a list of callback functions to perform various task during boosting. See callbacks. Some of the callbacks are automatically created depending on the parameters' values. User can provide either existing or their own callback methods in order to customize the training process.
- verbose If 0, xgboost will stay silent. If 1, xgboost will print information of performance. If 2, xgboost will print some additional information. Setting verbose > 0 automatically engages the cb.evaluation.log and cb.print.evaluation callback functions.
- num_class set number of classes in case of multiclassification problem
- weight a vector indicating the weight for each row of the input.
- na_missing by default is set to NA, which means that NA values should be considered as 'missing' by the algorithm. Sometimes, 0 or other extreme value might be used to represent missing values. This parameter is only used when input is a dense matrix.

Details: Create a new 'XGBTrainer' object.

Returns: A 'XGBTrainer' object.

Examples:

```
library(data.table)
df <- copy(iris)
```

```
# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
```

Method `cross_val()`:

Usage:

```
XGBTrainer$cross_val(X, y, nfolds = 5, stratified = TRUE, folds = NULL)
```

Arguments:

X data.frame

y character, name of target variable

nfolds integer, number of folds

stratified logical, whether to use stratified sampling

folds the list of CV folds' indices - either those passed through the folds parameter or randomly generated.

Details: Trains the xgboost model using cross validation scheme

Returns: NULL, trains a model and saves it in memory

Examples:

```
\dontrun{
library(data.table)
df <- copy(iris)
```

```
# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1
```

```
# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
```

```
# do cross validation to find optimal value for n_estimators
xgb$cross_val(X = df, y = 'Species',nfolds = 3, stratified = TRUE)
}
```

Method `fit()`:

Usage:

```
XGBTrainer$fit(X, y, valid = NULL)
```

Arguments:

X data.frame, training data
 y character, name of target variable
 valid data.frame, validation data

Details: Fits the xgboost model on given data

Returns: NULL, trains a model and keeps it in memory

Examples:

```
library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
xgb$fit(df, 'Species')
```

Method predict():*Usage:*

```
XGBTrainer$predict(df)
```

Arguments:

df data.frame, test data set

Details: Returns predicted values for a given test data

Returns: xgboost predictions

Examples:

```
# library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
xgb$fit(df, 'Species')

# make predictions
preds <- xgb$predict(as.matrix(iris[,1:4]))
```

Method show_importance():*Usage:*

```
XGBTrainer$show_importance(type = "plot", topn = 10)
```

Arguments:

```
type character, could be 'plot' or 'table'
topn integer, top n features to display
```

Details: Shows feature importance plot

Returns: a table or a plot of feature importance

Examples:

```
\dontrun{
library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)

xgb$fit(df, 'Species')
xgb$show_importance()
}
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
XGBTrainer$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

Examples

```
## -----
## Method `XGBTrainer$new`
## -----

library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
```

```

        maximize = FALSE,
        eval_metric = 'merror',
        num_class=3,
        n_estimators = 2)

## -----
## Method `XGBTrainer$cross_val`
## -----

## Not run:
library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)

# do cross validation to find optimal value for n_estimators
xgb$cross_val(X = df, y = 'Species',nfolds = 3, stratified = TRUE)

## End(Not run)

## -----
## Method `XGBTrainer$fit`
## -----

library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
xgb$fit(df, 'Species')

## -----
## Method `XGBTrainer$predict`
## -----

#' library(data.table)
df <- copy(iris)

```

```
# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
xgb$fit(df, 'Species')

# make predictions
preds <- xgb$predict(as.matrix(iris[,1:4]))

## -----
## Method `XGBTrainer$show_importance`
## -----

## Not run:
library(data.table)
df <- copy(iris)

# convert characters/factors to numeric
df$Species <- as.numeric(as.factor(df$Species))-1

# initialise model
xgb <- XGBTrainer$new(objective = 'multi:softmax',
                      maximize = FALSE,
                      eval_metric = 'merror',
                      num_class=3,
                      n_estimators = 2)
xgb$fit(df, 'Species')
xgb$show_importance()

## End(Not run)
```

Index

* datasets

cla_train, 3
reg_train, 35

bm_25, 2

cla_train, 3
Counter, 3
CountVectorizer, 4

dot, 7
dotmat, 8

GridSearchCV, 9

kFoldMean, 11
KMeansTrainer, 13
KNNTrainer, 16

LabelEncoder, 20
LMTrainer, 23

NBTrainer, 29
normalise1d, 31
normalise2d, 32

R6Class, 16, 20
RandomSearchCV, 33
reg_train, 35
RFTrainer, 36

smoothMean, 40
sort_index, 41
superml::CountVectorizer, 42
superml::GridSearchCV, 33

TfidfVectorizer, 42

XGBTrainer, 46